

CLAIMS

We claim:

- 5 1. An inspection device including:
 a light source;
 a pellicle beamsplitter for receiving light from the light source and
redirecting said light;
 an aperture array for receiving light from the pellicle beamsplitter;
 a dual telecentric object reimager including a plurality of lenses;
10 a telecentric camera imager including a plurality of lenses; and
 a camera for collecting focused light.
- 15 2. A process of inspecting a surface including bumps thereon, the
process comprising:
 scanning a surface using optics and a camera capable of
determining light intensity for each pixel viewed;
 measuring the light intensity at each pixel at a first elevation;
 measuring the light intensity at each pixel at a second elevation;
and
20 determining the elevation of the surface using a Gaussian curve
based upon the light intensities measured at the first and second elevations at
each pixel .
- 25 3. The process of claim 2 further comprising:
 scanning at least particular portions of a surface believed to
contain protrusions extending outward from the surface using optics and a
camera capable of determining light intensity for each pixel viewed;
 measuring the light intensity at each pixel at a third elevation;
 measuring the light intensity at each pixel at a fourth elevation; and
30 determining the elevation of the protrusions using a gaussian curve
based upon the light intensities measured at the third and fourth elevations at
each pixel .
- 35 4. The process of claim 3 further comprising:
 determining the height of a protrusion by calculating the difference
between the elevation of a protrusion and the elevation of the surface.

5. The process of claim 2 wherein an inspection device is used to perform the scanning and includes:

a light source;

5 a beamsplitter for receiving light from the light source and redirecting said light;

an aperture array for receiving light from the pellicle beamsplitter;

at least one reimager; and

a camera for collecting focused light.

10